

WALL PACK ETH SERIES

Product Description

Etherium Wall Packs luminaire is energy efficient yet powerful enough to replace up to 400W metal halide fixtures while saving up to 80% in energy costs. Our rugged die-cast housing provides advanced thermal management and weather proof gaskets to withstand any extreme outdoor environments.



FEATURES
Half Cut Glass Lens
40W / 60W / 80W / 100W
4000K / 5000K
Efficacy up to 146 LPW
0 – 10V Dimming
IP 65 Rating
DLC Premium
7 Year Warranty
Operation Temperature -20°C to 50°C

Construction & Installation

Made with die-cast aluminum housing with a tempered glass diffuser our LED Wall Pack Series have knock-outs on the housing for both motion sensors and photocell accessories. Boasts a back plate designed to be easily mounted to a 4" square junction box.

Electrical & Operations

Etherium Wall Packs comes with universal voltage (120-277V) equipped with 0-10V dimming capable premium driver. Can operate in temperatures -20°C to 50°C. Surge immunity 4kV

Applications

Outdoor wall-mount, retail shopping malls, exterior commercial and industrial applications.

Certification

UL Listed. All components have UL certification. UL Class 2. Driver: SCP, OTP, OVP protection, FCC Part 15 Class B, UL8750 Class 2. DLC Premium. IP 65

Warranty

7 year warranty with a 75,000 hour rated L70. See warranty documentation for more detail information



ORDERING INFORMATION

Example: ETH-E02-60W-H-4000K


Nomenclature	Series	Form Factor	Wattage	Voltage	Color Temp
ETH	E	02	60W	H	4000K
ETH = Etherium	E = Wall Pack Series	02, 03 = Glass Lens	40W = 40 Watts 60W = 60 Watts 80W = 80 Watts 100W = 100 Watts	H = 120-277v	4000K = 4000K 5000K = 5000K

Specifications and Dimensions subject to change without notice


SPECIFICATION	
PERFORMANCE SUMMARY	
Input Voltage	120V-277V
Input Frequency	50/60 Hz
Wattage	See Performance table
Lumens	See Performance Table
Efficacy	>146 LPW
CRI	80+
CCT	4000K / 5000K
IP Rating	65
Rated Life	75,000 Hr
L70	>72,000 Hr
Power Factor	>0.9
THD	<15%
Dimming	0-10V
Operating Temp.	-20°C to 50°C

DIMENSIONS

Front View



Side View



ACCESSORIES	
SENSORS	
Model No.	Description
WP-DLPC	Daylight Harvesting
WP-OS	Occupancy

CARTON DIMENSIONS AND WEIGHT			
Model	Carton	Weight	PCS/BOX
40W	15.75" x 11.0" x 9.3"	9.0 LBS	1 pcs
60W / 80W	15.75" x 11.0" x 9.3"	9.2 LBS	1 pcs
100W	15.75" x 11.0" x 9.3"	9.7 LBS	1 pcs

PERFORMANCE DETAILS				4000K		5000K	
Form Factor	Catalog No.	Rated Wattage	Tested Wattage	Total Lumens	Efficacy LPW	Total Lumens	Efficacy LPW
02	ETH-E02-40W-H	40W	40W	5760 lm	144	5800 lm	145
02	ETH-E02-60W-H	60W	63.46W	9149 lm	144.5	9252 lm	145.7
03	ETH-E03-80W-H	80W	79.57W	11567 lm	145.3	11637 lm	146.6
03	ETH-E03-100W-H	100W	100W	14400 lm	144	14500 lm	145

Specifications and Dimensions subject to change without notice