

## PRODUCT DESCRIPTION:


Industrial and commercial applications. For road and area lighting like: parking decks, auto dealerships, high masts, apartments, residential complexes, shopping malls, sporting complexes and fields, educational facilities, streets, roadways, parks, recreational bike paths, and municipal lots.

## FEATURES:

- Philips Lumileds 3030 LED chips
- Heavy duty die-cast aluminum housing
- fully sealed with an IP rating of 65
- High quality tempered glass optics
- Polyester powder-coated finish, rust and corrosion proof; stabilized to extreme climate changes without cracking or peeling


## DIMENSIONS:

### DIMENSION Inch(mm)



## Wall Pack 50W Spec

LOD-AWP-50W-50K-LV-V12



### SPECIFICATIONS:

SPECIFICATION	Details
Model	LOD-AWP-50W-50K-LV-V12
Input Wattage (W)	50W
Lumens Delivered (LM)	4,680LM
Efficacy (LM/W)	117LM/W
CRI	70
Lifespan	50,000 hours
Color Temperature	5,000K
Wattage Equivalent	100W
Dimmable	Yes
IP Rating	IP65
Beam Angle	100
Input Voltage	AC120-277V
Power Factor	0.96
Housing	Aluminum
Lens	Frosted
Mounting	Wall Surface
THD	9.7%
Size	8.25" x 6.6" x 3.8"
Certification	DLC, ETL
Operating Temperature	-40°C to 40°C
Environment	Outdoor
Warranty	5 years limited

### OPTIONAL ACCESSORIES



10KV SPD  
120-277V



BUTTON STYLE  
PHOTOCELL  
120-277V



DIMMABLE MOTION  
SENSOR  
120-277V

### INSTALLATION

