

## PRODUCT DESCRIPTION:

Industrial and commercial applications. For road and area lighting like: parking decks, auto dealerships, high masts, apartments, residential complexes, shopping malls, sporting complexes and fields, educational facilities, streets, roadways, parks, recreational bike paths, and municipal lots.

## FEATURES:

- Philips Lumileds 3030 LED chips
- Heavy duty die-cast aluminum housing with quick mount back plate for easy installation
- fully sealed with an IP rating of 65
- High quality tempered glass optics
- Integral secondary heat sink to optimize thermal transfer and maximize performance and life of LED
- Driver is mounted in direct contact with the casting for low operating temperature and long life.
- Polyester powder-coated finish, rust and corrosion proof; stabilized to extreme climate changes without cracking or peeling

## DIMENSIONS:

## Wall Pack 60W Spec

LOD-WP-60WSAD50K-HLV2



**SPECIFICATIONS:**

SPECIFICATION	Details
Model	LOD-WP-60WSAD50K-HLV2
Input Wattage (W)	60W
Lumens Delivered (LM)	7,760LM
Efficacy (LM/W)	129LM/W
CRI	70
Lifespan	50,000 hours
Color Temperature	5,000K
Wattage Equivalent	175W - 250W HID
Dimmable	Yes
IP Rating	IP65
Beam Angle	120
Input Voltage	AC120-277V
Power Factor	0.9
Housing	Aluminum
Lens	Frosted
THD	20%
Mounting	Wall Surface
Weight (LBS)	8.37lbs
Size	14.3" x 9.2" x 7.52"
Certification	DLC, ETL, FCC, CE RoHS, TUV, ISO9001
Operating Temperature	-20°C to 50°C (-4°F to 122°F)
Environment	Outdoor
Warranty	5 years limited

**OPTIONAL ACCESSORIES:**

Cut off shield

**CONTROLS:**

Photocell optional

Motion sensor optional

