

PRODUCT DESCRIPTION:

T8 linear tube retrofits are usually but not specifically used in commercial buildings such as hotels, conference rooms, schools, supermarkets, factory, parking garages, hospitals, airport, metro stations, bus stations, office buildings and any other sites where request long-time and hi-output lighting.

FEATURES:

- NSF Approved
- Double ended Type A
- Single ended Type B
- Shatterproof glass
- Input voltage is AC110V-277V
- Low thermal decay
- Low maintenance
- No mercury, lead-free
- No UV

Shatterproof Glass Plug & Play Tube 4FT 12W Spec

LOD-GDMT84F-12W40KF



SPECIFICATIONS:

SPECIFICATION	Details
Model	LOD-GDMT84F-12W40KF
NSF #	LOD-4FTT8GP-12W40K
Input Wattage (W)	12W
Lumens Delivered (LM)	1,800LM
Efficacy (LM/W)	150LM/W
CRI	80
Lifespan	50,000 hours
Color Temperature	4,000K
Wattage Equivalent	32W – 36W
Dimmable	No
IP Rating	IP40
Beam Angle	270
Input Voltage	AC110-277V
Power Factor	0.9
Housing	Glass
Lens	Frosted
Mounting	G13
Size	48"
THD	10%
Certification	DLC, UL, NSF
Operating Temperature	-20°C to 50°C (-4°F to 122°F)
Environment	Indoor
Warranty	5 years limited

