

PRODUCT DESCRIPTION:

T8 linear tube retrofits are usually but not specifically used in commercial buildings such as hotels, conference rooms, schools, supermarkets, factory, parking garages, hospitals, airport, metro stations, bus stations, office buildings and any other sites where request long-time and hi-output lighting.

FEATURES:

- LED Chip BXEN-27E-11M-3A
- NSF approved
- Type B Single or Double Ended
- Plug & Play Dual Mode (type A & B)
- Shatterproof glass
- Input voltage is AC110V-277V
- Low thermal decay
- Low maintenance
- No mercury, lead-free
- No UV

Shatterproof Proof Tube 4FT 15W Spec

LOD-GDMT84F-15W40KF YM2

LOD-GDMT84F-15W50KF YM2



SPECIFICATIONS:

SPECIFICATION	Details	
Model	LOD-GDMT84F-15W40KF YM2	LOD-GDMT84F-15W50KF YM2
Input Wattage (W)	15W	
Lumens Delivered (LM)	2,100LM	2,100LM
Efficacy (LM/W)	140LM/W	140LM/W
CRI	80	80
Lifespan	50,000 hours	
Color Temperature	4,000K	5,000K
Wattage Equivalent	32W – 36W	
Dimmable	No	
IP Rating	IP40	
Beam Angle	240	
Input Voltage	AC110-277V	
Power Factor	0.9	0.9
Housing	Glass + Shatterproof Film	
Lens	Frosted	
Mounting	G13	
Size	48"	
THD	20%	20%
Certification	DLC, UL, NSF	
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	
Environment	Indoor	
Warranty	5 years limited	

