

PRODUCT DESCRIPTION:

T8 linear tube retrofits are usually but not specifically used in commercial buildings such as hotels, conference rooms, schools, supermarkets, factory, parking garages, hospitals, airport, metro stations, bus stations, office buildings and any other sites where request long-time and hi-output lighting.

FEATURES:

- LED Chip SOM2835
- Type B Single Ended or Type B Double Ended
- Shatterproof glass
- Input voltage is AC110V-277V
- Low thermal decay
- Low maintenance
- No mercury, lead-free
- No UV

Shatterproof Glass Internal Tube 4FT 12W Spec

LOD-GDMT84F-12W40KF B

LOD-GDMT84F-12W50KF B



SPECIFICATIONS:

SPECIFICATION	Details	
Model	LOD-GDMT84F-12W40KF B	LOD-GDMT84F-12W50KF B
Input Wattage (W)	12W	
Lumens Delivered (LM)	1,860LM	1,860LM
Efficacy (LM/W)	155LM/W	155LM/W
CRI	80	80
Lifespan	50,000 hours	
Color Temperature	4,000K	5,000K
Wattage Equivalent	32W – 36W	
Dimmable	No	
IP Rating	IP40	
Beam Angle	160	
Input Voltage	AC110-277V	
Power Factor	0.9	0.9
Housing	Glass	
Lens	Frosted	
Mounting	G13	
Size	48"	
THD	20%	20%
Certification	DLC, UL, NSF	
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	
Environment	Indoor	
Warranty	5 years limited	

