



## SPECIFICATION FEATURE:

THE HOUSING IS MADE OF REINFORCED POLY-ESTER FIBERGLASS WITH METAL LATCHES.

CLEAR AND OPAL DIFFUSER ARE OPTIONAL

BUILD WITH 5VA MATERIALS.

WATER-PROOF. DUST-PROOF, SHATTER PROOF AND CORROSION-PROOF

MOTION SENSOR AND BATTERY BACKUP ACCESSORY OPTIONS

STANDARD 0-10V DIMMING AVAILABLE

**4FT**

**40W - 56W**

INPUT VOLTAGE	110 - 277 VAC
CRI	>80
LUMEN PER WATT	40W - 115 LM/W 56W - 114 LM/W
AVAILABLE CCT	4000K,5000K
LIFE SPAN	50,000 HOURS
OPERATION TEMPERATURE	-40°F ~ 113°F
LUMEN	40W - 4600 56W - 6400
MOUNTING OPTIONS	SURFACE MOUNT



## ORDERING OPTIONS:

# 4 FEET 40W - 56W

EXAMPLE: LED2AVT 4FT 40W 50K

LED2AVT	4FT 40WATT	50K	-[BLANK]	-[BLANK]	-[BLANK]
<b>SERIES</b>	<b>RATED WATTAGE &amp; DIMENSION</b>	<b>COLOR TEMP</b>	<b>INPUT VOLTAGE</b>	<b>SENSOR</b>	<b>BACKUP BATTERY</b>
LED2AVT	4FT 40W 4 FEET 40 WATT 4FT 56W 4 FEET 56 WATT	40K 4000KELVIN 50K 5000KELVIN	BLANK 110 - 277 VAC	BLANK NO SENSOR MS MOTION SENSOR	BLANK -NO BATTERY EB -EMERGENCY BATTERY



The luminaire with throughout cable, two glands and terminals to make connect in series.