

Fixture Type:

Project Name:

Location:



Date:

Features

- Medium LED flood light with 7H*6V NEMA distributions
- Rugged die-cast aluminum housing
- Vented housing separated LEDs module from driver, maximizing fixture lifespan and performance
- Door frame seals to housing with a continuous extruded silicone gasket
- Slipfitter or trunnion mount option
- Compatible with photocell



Dimension



Product Performance Standard

Size	5" L X 8" W X 3 1/8" H	Power Factor	≥90%
Weight	3 lb	LED Lifespan	50,000 Hrs
IP Rate	IP65	Dimmable	Non Dimmable
Color Temp	4000K-5000K	NEMA Type	7H*6V
CRI	70	Warranty	5 Years
Input Voltage	120-277V	Ambient Operation Temperature	-40C° (-40°F) ~40C° (104°F)

Ordering Guide Example: LEDMFL 45W 40K

Fixture Type	Wattage	Color Temp.	Voltage	Finish	Mounting	Optional Accessories
LEDMFL	45W 60W	40K=4000K 50K=5000K	Blank = 120-277V	Blank = Dark Bronzed BK = Black WH = White	TM = Trunnion KN = Knuckle	Blank = No Accessories PC = Photocell (-WPPC)



Fixture Type:
Project Name:
Location:
Date:

Product Information

4000K			5000K	
WATTAGE	LUMEN	EFFICACY	LUMEN	EFFICACY
45W	5650lm	123lm/W	5700lm	126lm/W
60W	7250lm	121m/W	7450lm	124lm/W

Optional Accessories



Internal Photocell

- SKU: WPPC
- Internal photocell is field installed or pre-installed by request.


For the accessories detail, please visit www.lironlighting.com/product_categories/add-on-accessories

Mounting Options




Knuckle Mount

-SKU: KN



Trunion Mount

-SKU: TM





Fixture Type:
Project Name:
Location:
Date:

Wiring Diagram

CORD/ SUPPLY WIRING

LUMINAIRE



Scan the QR code or visit www.lironlighting.com/products/ledmfl for the complete luminaire installation guide.

Note:
