

## PRODUCT DESCRIPTION:

T8 linear tube retrofits are usually but not specifically used in commercial buildings such as hotels, conference rooms, schools, supermarkets, factory, parking garages, hospitals, airport, metro stations, bus stations, office buildings and any other sites where request long-time and hi-output lighting.

## FEATURES:

- Type B
- Input voltage is AC120V-277V
- Low thermal decay
- Shatter-proof design
- Low maintenance
- No UV emission

## 3ft Tube 12W Spec

LOD-12WT83FT-40KB

LOD-12WT83FT-50KB



### SPECIFICATIONS:

SPECIFICATION	Details	
Model	LOD-12WT83FT-40KB	LOD-12WT83FT-50KB
Input Wattage (W)	12W	
Wattage Equivalent	32W – 36W	
Lumens Delivered (LM)	1,402.48LM	1,440.08LM
Efficacy (LM/W)	118.7LM/W	122.77LM/W
CRI	80	80
THD	15%	15%
Color Temperature	4,000K	5,000K
Power Factor	0.9	0.9
Dimmable	No	
IP Rating	IP40	
Beam Angle	320	
Input Voltage	AC120-277V	
Housing	PC + Aluminum	
Lens	Glass Coating	
Mounting	G13	
Size		
Lifespan	50,000 hours	
Certification	DLC, UL	
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	
Environment	Indoor	
Warranty	5 years limited	

3,000K & 3,500K are special order

