

PRODUCT DESCRIPTION:

T8 linear tube retrofits are usually but not specifically used in commercial buildings such as hotels, conference rooms, schools, supermarkets, factory, parking garages, hospitals, airport, metro stations, bus stations, office buildings and any other sites where request long-time and hi-output lighting.

FEATURES:

- Type A
- Input voltage is AC100V-277V
- Low thermal decay
- Low maintenance
- No UV emission

Plug & Play Tube 4ft 17W Spec

[LOD-4FT17WC-40KA](#)

[LOD-4FT17WC-50KA](#)

[LOD-4FT17WF-40KA](#)

[LOD-4FT17WF-50KA](#)



SPECIFICATIONS:

SPECIFICATION	Details			
Model	LOD-4FT17WC-40KA	LOD-4FT17WC-50KA	LOD-4FT17WF-40KA	LOD-4FT17WF-50KA
Input Wattage (W)	17W			
Wattage Equivalent	32W – 36W			
Lumens Delivered (LM)	2,200LM	2,200LM	2,145LM	2,145LM
Efficacy (LM/W)	125LM/W	125LM/W	122LM/W	122LM/W
CRI	81.5	81.5	80	80
THD	10.2%	10.2%	20%	20%
Color Temperature	4,000K	5,000K	4,000K	5,000K
Power Factor	0.992	0.992	0.9	0.9
Lens	Clear	Clear	Frosted	Frosted
IP Rating	IP40			
Beam Angle	120			
Input Voltage	AC100-277V			
Housing	Aluminum			
Dimmable	No			
Mounting	G13			
Size				
Lifespan	50,000 hours			
Certification	DLC, UL			
Operating Temperature	-20°C to 50°C (-4°F to 122°F)			
Environment	Indoor			
Warranty	5 years limited			

3,000K & 3,500K are special order

